


Data Sheet

Wired Floor Heating Master Controller

Description



Olgassys master controller , is a junction box used in hydronic floor heating systems supplied from a manifold.

Master control unit is a wiring hub that connects thermal actuators to room thermostats. It provides two relays that control a circulation pump and a boiler.

Relays activate when one or more thermostats need heat. The controller has 8 outlets and is connected to 230 VAC/50 Hz. There are led indicators that show the operating status of circuits.


Ordering

Product	Supply Voltage	Output Voltage	Number of actuators and type	Ordering Code
wired master control unit	230 VAC	230 VAC	16 / NC	OLG1800


Technical data

Supply voltage	230 VAC $\pm$ 10%
Output number	8
Output voltage	230 VAC
Max. load per output	3 W (2 actuator)
Pump / boiler relay	max load 230 VAC (2A)
Ambient temperature	0 - 50° C
IP class	20

System Scheme



Dimensions



Olgassys can accept no responsibility for possible errors in catalogues, brochures and other printed material. Olgassys reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without subsequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Olgassys and all Olgassys logotypes are trademarks of Olgassys Ltd.Sti.. All rights reserved.