#### **Data Sheet**

# **Thermal Actuator**

# **Description**



Thermal actuator is used with 2 way motorized control valves, automatically balanced combination valves and automatically controlled floor heating manifolds.

The actuator can be controlled with an on/off controller or switch.

These provide a cost effective solution for the control of hot and/or chilled water for fan coil units, small reheaters and recoolers, floor heating zones temperature control systems.

# ( (

#### **Main features**

- 24VAC/Dc or 230 VAC supply
- Position indicator
- Normally closed NC
- Medium temperature 120 C
- · Cable included

# **Ordering**

Product	Туре	Supply Voltage	Ordering Code
Thermal actuator	NC	230 VAC	OLG1816
Thermal actuator	NC	24 VAC / DC	OLG1817




#### **Technical data**

Power supply	V	24 VAC/DC ± 25%	230 VAC ± 25%
Power consumption	W	2	
Frequency	Hz	50/60	
Control input		on/off	
Closing force	N	110	
Min. stroke	mm	3	
Full stroke time	min	2.4	
Max. medium temperature	° C	120	
Ambient temperature	° C	260	
IP class		IP 41	
Cable lenght	m	1.2	


# Operation

Thermal actuator works on the thermal expansion principle:

- moves actuator stem in one direction in case of heating of the actuator and
- moves actuator stem in another direction in case of no heating of the actuator
- NC version, in the non-energized state actuator's stem is extracted
- Actuator has an internal spring, which is factory fixed with a split ring (Fig.1) to hold the spring retracted in its off -the-shelf state.
  The use of split ring allows the actuator to be mounted to the valve. Once mounted, the split ring has to be removed.



• The actuator is equipped with a position indicator to show the position of the actuator stem (*Fig.2*).







# Installation

#### Mechanical

Installation of the valve with the actuator is allowed in horizontal position or upwards.



# Electrical



#### **Dimensions**

